

DATASHEET



OS009

IP20 360° PIR Sensor - Recess Mounting

www.mlaccessories.co.uk

MLA PART CODE	OS009
DESCRIPTION	IP20 360° PIR Sensor - Recess Mounting
NET WEIGHT (KG)	0.083
FINISH	White
DIMENSIONS (MM)	Diameter - 76 Recessed Depth - 58
CUT-OUT (MM)	Cut-out Diameter - 62
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
IC RATED	No
OPERATING TEMPERATURE	-20 to 40°C
INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD	1200W Incandescent / 300W LED
ADDITIONAL FEATURES	Standby Power 0.1W. Optimum installation height 2.2 to 4m
FUNCTION	Adjustable Lux, Adjustable Time
SENSOR TYPE	PIR
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	360
OPTIMUM DETECTION RANGE (M)	6 @ 2.4m height
SENSOR DURATION	10 seconds to 8 minutes
SENSOR LUX SETTINGS	3 - 2000 lux
WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH	EN 60669-2, EN 60669-1
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832930419

Date Created: 07/01/2022 15:12